



2/3" 1.4/16mm C		1/2"	1/3"
FOCAL LENGTH		f=16mm	
MAX. DIAMETER (RATIO)		F=1:1.4~16	
ELEMENT		6Gr6 Element	
PICTURE SIZE		6.6x8.8mm	4.8x6.4
ANGLE	VER. ANGLE	22.8°	16.6°
	HOR. ANGLE	30.5°	22.2°
	DIA. ANGLE	38.3°	27.7°
DISTORTION		-1.5%	-0.8%
SHOOTING RANGE AT	VER.	82.6mm	59.6mm
MINIMUM FOCUS	HOR.	111.8mm	80.1mm
DISTANCE	DIA.	142.5mm	101.1mm
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		12.15mm in air	
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		Front ϕ 12.0mm	Rear ϕ 12.8mm
MOUNT		C-MOUNT	
EXIT PUPIL		-48.9mm	
TEMPERATURE RANGE		-10~+45° C	
STORING TEMPERATURE RANGE		-40~+60° C	
RESOLUTION CENTER/CORNER		Center 100 /mm	Corner 40 Lp/mm

		LM16JC	
		2/3" 1.4/16mm	